

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

CR-171 698


C.1

(NASA-CR-171698) SERVO CONTROLLED VARIABLE
PRESSURE MODIFICATION TO SPACE SHUTTLE
HYDRAULIC PUMP Final Technical Report (Abex
Corp., Oxnard, Calif.) 35 p HC A03/MF A01

N83-35002

Unclass

CSCL 22B G3/16 42181



Abex Corporation - Aerospace Division
3151 W. 5th St., Oxnard, California 93030



Abex

An **IC Industries** Company

**Aerospace
Division**

ORIGINAL PAGE IS
OF POOR QUALITY

FINAL TECHNICAL REPORT
TO
NASA, L. B. JOHNSON SPACE CENTER
ON
SERVO CONTROLLED, VARIABLE PRESSURE
MODIFICATION TO
SPACE SHUTTLE HYDRAULIC PUMP
NASA CONTRACT
NAS 9-16622

AER-873
25 July 1983

Prepared by:

H. H. Kouns

H. H. Kouns
Staff Engineer

Approved by:

T. E. Sarphie
for

T. E. Sarphie
Director of Engineering

Aerospace
Division

Alex

An IC Industries Company

TABLE OF CONTENTS

| | <u>Page No.</u> |
|--|-----------------|
| INTRODUCTION | 1 |
| OBJECTIVE. | 1 |
| DESCRIPTION OF PUMP MODIFICATIONS. | 1 |
| RVDT CALIBRATION | 7 |
| PUMP PERFORMANCE & RESPONSE CHARACTERISTICS. | 9 |
| CONCLUSIONS. | 18 |

LIST OF ILLUSTRATIONS

| | |
|--|----|
| Installation Drawing 65155 - Pump Hydraulic Variable | |
| Delivery | 2 |
| Figure 1 - Rotary Variable Displacement Transducer . . | 4 |
| Figure 2 - Servo-Controlled Variable Pressure | |
| Compensator. | 6 |
| Figure 3 - RVDT Calibration. | 8 |
| Figure 4 - Calibration - AP27VP-2. | 10 |
| Figure 5 - Calibration - AP27VP-2. | 11 |
| Figure 6 - Calibration - AP27VP-2. | 12 |
| Figure 7 - Calibration - AP27VP-2. | 13 |
| Figure 8 - Calibration - AP27VP-2. | 14 |
| Figure 9 - Calibration - AP27VP-2. | 15 |

LIST OF ILLUSTRATIONS - continued

Page No.

| | |
|--|----|
| Figure 10 - Calibration - AP27V-7. | 16 |
| Figure 11 - Calibration - AP27V-7. | 17 |
| Figure 12 - Photos - Response Time - AP27VP-2. | 19 |
| Figure 13 - Photos - Response Time - AP27VP-2. | 20 |
| Figure 14 - Pressure Control Hysteresis. | 21 |
| Figure 15 - Pressure Control Hysteresis. | 22 |
| Figure 16 - Pressure Control Hysteresis. | 23 |
| Figure 17 - Pressure Control Hysteresis. | 24 |

APPENDIX

INTRODUCTION

This report describes the modifications made to a standard model AP27V-7 (Abex P/N 65111) Space Shuttle hydraulic pump under contract NAS 9-16622 for the L.B. Johnson Space Center at Houston, Texas.


OBJECTIVE

The objective of the contract is to modify the constant pressure control of the model AP27V-7 hydraulic pump to an electrically controlled variable pressure setting compensator. In addition, the conversion is to include a hanger position indicator for continuously monitoring hanger angle. Also to be furnished is a simplex servo driver for controlling the pressure setting servovalve, as well as a support data package. Pump is then to be used to evaluate integrated performance on an "iron bird" flight control system application.

DESCRIPTION OF PUMP MODIFICATIONS

Drawing number 65155 shows the pertinent overall and installation dimensions of the model AP27VP-2 pump. All basic port dimensions are unchanged from the -7 model. The pump overall length has been increased to 10.8 inches and the vertical height from the pump center line has been increased to 6.09 inches to accommodate the RVDT unit. Other specifications remain unchanged.

ORIGINAL PAGE IS
OF POOR QUALITY



UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE IN INCHES
THE FINISHES IS TO BE UNLESS NOTED
DIMENSIONS ARE TO BE AS SHOWN AND
CONFORM TO THE FOLLOWING
ALL FINISHED SURFACES UNLESS NOTED
FINISHES SHALL CONFORM TO THE
FINISHES TO BE CONFORM TO THE
DIMENSIONS AND FINISHES
A. FINISHES SHALL BE AS SHOWN
UNLESS NOTED OTHERWISE
MATERIALS

| | | | | | |
|--|--|-----------------|--|--|--|
| NAME CHAMBERLAIN ADDRESS RIVERVIEW AVE LOS ANGELES CALIFORNIA | | | | ALEX CORPORATION ATTENTION: DIRECTOR 3101 West 6th Street Compton, California 90221 | |
| ORDER NO. DATE PUMP-HYDRAULIC VARIABLE DELIVERY INSTALLATION OF | | SIZE D 75250 | | DRAWING NUMBER 65155 | |



RATED CURRENT _____ 8MA, 2CMA MAX
COIL RESISTANCE _____ 1000 OHMS (EA)
MAGNETIC BIAS EQUIVALENT TO _____ 2 MA

NOTES

The basic unit furnished by NASA was a modified version of the standard Shuttle hydraulic pump (part number 65111, S/N 152294). The pump was disassembled and inspected for wear; all parts were found to be in excellent condition. The port plate was discarded, however, because it was a non-standard configuration (a result of an earlier special modification). A new port plate of standard configuration was substituted.

The pump mounting flange and hanger were then modified for adapting the RVDT (rotary variable displacement transducer) unit which is mounted on a special pad at the end of the mounting flange. Figure 1 is a partial cross section of the RVDT and mounting pad. The hanger angle position shaft is driven by a pinion gear which engages a segment gear at the end of the hanger. The resulting drive train ratio is 1:3. The other end of the position shaft is connected through a flexible coupling to the RVDT. The shaft is supported by a ball bearing and is sealed externally with a lip seal.

The pump front housing was modified by the addition of trunnion bearing stops which were welded and machined to form cradles above each bearing. These stops limit hanger lift under start up or adverse, no-load conditions to a maximum of .010 inches. This prevents disengagement of the hanger position indicator gears.




ORIGINAL PAGE IS
OF POOR QUALITY

ROTARY VARIABLE DISPLACEMENT TRANSDUCER

Figure 1

A new port cap was designed and fabricated to give point to point inlet and outlet port locations and sizes per the AP27V-7 installation requirements and to accommodate the mounting of the servovalve. The design included the proven variable pressure control concept adapted from a similar size Abex pump.

Figure 2 is a schematic cross section of the pressure control mechanism and servovalve. The normally stationary sleeve of the compensator is now movable. The position of the sleeve, as shown, is in the maximum set pressure position. In this mode the compensator spool is load-adjustable with the normal adjusting screw-spring loading mechanism; maximum operating pressure is adjusted with the sleeve in this position. Fitted to the sleeve at the larger end is a floating piston grounded against the end cap. The net area of this piston is biased against the step area on the outside of the control sleeve. Pressure on the sleeve step area is controlled by the servovalve through the receiver. If the servovalve receives a command to reposition the sleeve to the right (lower pressure), the jet repositions to increase the receiver pressure and the sleeve moves to the right until rebalance is achieved between the floating piston of the sleeve and the step area of the sleeve. A position feedback spring between the sleeve and the servovalve jet pipe closes the command loop of the control system. Repositioning the



SERVO-CONTROLLED VARIABLE PRESSURE COMPENSATOR

Figure 2


ORIGINAL PAGE IS
OF POOR QUALITY

compensator sleeve to the right is equivalent to decreasing the spool spring load by unscrewing the adjustment screw an equivalent amount to the left. Basically, the compensator spool pressure, the floating piston pressure, and servovalve supply pressure are all equal to pump discharge pressure. The receiver pressure and the step area pressure are servovalve controlled.

The control concept is "fail safe" in that any interruption of electrical signal (zero amperage) or hydraulic supply pressure (plugged filter) to the servovalve results in a pressure bias on the compensator sleeve such that it immediately repositions against the stop to the left (high pressure setting).

RVDT CALIBRATION

Figure 3 is a calibration curve of the RVDT output voltage vs hanger angle of the pump. The voltage change is linear from the zero-stroke hanger angle to the maximum-stroke angle of 19.4 degrees. RVDT voltage outputs are - 3.8 volts and + 3.66 volts, respectively. At elevated pump temperatures, the maximum stroke angle of the hanger increases slightly ($0.1 - 0.2^{\circ}$), as will the voltage output of the RVDT.



Abex

Aerospace
Division

RVDT CALIBRATION

Figure 3


An IC Industries Company

PUMP PERFORMANCE & RESPONSE CHARACTERISTICS

A series of pump calibration data were taken on the AP27VP2 unit at 3917 rpm and at inlet temperatures of 150 F and 225 F. Torque and hanger position voltages were recorded at discharge pressure levels of 3000, 2000, and 1000 psi and at flows from full flow to zero gpm in 25 percent intervals. The results of these data and pertinent calculations are shown by the calibration curves, Figures 4 through 9.

Performance of the unit at the 3000 psi level is essentially unchanged. Overall efficiency at 60 gpm is 87.5 percent, and heat rejection at 5 and 15 gpm is 380 btu/minute and 400 btu/minute, respectively, with an inlet temperature of 150 F. At the high inlet of 225 F, the efficiency at 60 gpm is 88 percent, and the heat rejection is 330 btu/minute and 332 btu/minute, respectively. At 225 F inlet, and 1000 psi discharge pressure, the comparable heat rejection at 5 and 15 gpm is 200 btu/minute and 240 btu/minute, respectively. This represents a 40 and 32 percent energy savings, respectively, at the lower pressure. Similar energy savings result throughout the complete flow range. Figures 10 and 11 are typical calibration curves of standard AP27V-7 Shuttle pump, included for comparison purposes.

The dynamic response of the pump output control circuit was determined by oscillograph traces of the discharge pressure as the electrical signal to the servovalve was interrupted




ORIGINAL PAGE IS
OF POOR QUALITY

Aerospace
Division

CALIBRATION ~ AP27VP-2

FIGURE 4

5-24-83 HK




Aerospace
Division

CALIBRATION ~ AP27VP-2

5-24-83 HK

FIGURE 5


12

ORIGINAL PAGE IS
OF POOR QUALITYAerospace
Division

CALIBRATION ~ AP27VP-2

5-24-83 HK

FIGURE 6




Aerospace
Division

CALIBRATION ~ AP27VP-2

5-24-83 HK

Figure 7



AP27VP-2
 ~ 2050 PSI
 3917 RPM
 225F

ORIGINAL PAGE IS
 OF POOR QUALITY


5-24-83 HK

Aerospace
 Division

CALIBRATION ~ AP27VP-2

FIGURE 8

15




ORIGINAL PAGE IS
OF POOR QUALITY

Aerospace
Division

CALIBRATION ~ AP27VP-2

FIGURE 9


5-24-83 HK



CALIBRATION AP27V-7

FIGURE 10

ORIGINAL PAGE 7
OF POOR QUALITY



CALIBRATION AP27V-7

FIGURE 11

ORIGINAL PAGE IS
 OF POOR QUALITY


and then restored. Traces were obtained at pump flows of 5 and 15 gpm and speeds of 1800 and 4000 rpm in a system volume of approximately 150 in³. Pressure recovery time (1000 psi to 3000 psi) varied from 47 ms (milliseconds) at the higher speed and lower flow to 107 ms at lower speed and the higher flow rate. Pressure stability was achieved well within the one second requirements of the military specification. Pressure decay times in most cases was approximately 70 ms (no requirement). Figures 12 and 13 are typical response traces photographs.

Pressure control hysteresis was determined at pump speeds of 1800 and 4000 rpm, with discharge flows of 5 and 15 gpm, and at an inlet temperature of 225 F. Control current hysteresis was generally less than 0.1 milliamperes. Figures 14 through 17 are typical performance plots of the electronic pressure control hysteresis.


CONCLUSIONS

Test results and data analysis confirm that the modified AP27VP-2 hydraulic pump meets or exceeds all of the requirements and objectives as described in the NASA contract. Normal (3000 psi) pump performance parameters are unchanged --output flow, overall efficiency, heat rejection, response, etc., are unaffected by the modifications. The expected

19



5 gpm, 1000-3000-1000 psi



15 gpm, 1000-3000-1000 psi


Speed ~1800 rpm
Sweep time ~200ms/block
Pressure ~ 500 psi/block

RESPONSE TIME - AP27VP-2


ORIGINAL PAGE IS
OF POOR QUALITY

Figure 12

20



5 gpm, 1000-3000-1000 psi




15 gpm, 1000-3000-1000 psi

Speed ~4000 rpm
Sweep time ~200ms/block
Pressure ~ 500 psi/block

RESPONSE TIME - AP27VP-2

Figure 13

ORIGINAL PAGE IS
OF POOR QUALITY


Abex


 Aerospace
Division

PRESSURE CONTROL HYSTERESIS

26 May 83 .HK

FIGURE 14

22



Abex

Aerospace
Division


PRESSURE CONTROL HYSTERESIS

26 May 83

.HK

Figure 15

23



Abex


Aerospace
Division

PRESSURE CONTROL HYSTERESIS

Figure 16

26 May 83

HK



AP27VP-2
5 GPM
4000 RPM
225F



Aerospace
Division

PRESSURE CONTROL HYSTERESIS

26 May 83

.HK

Figure 17

savings in heat rejection (energy reduction) are confirmed at the lower pressure levels. The electronic pressure level control functions properly with little hysteresis and the RVDT accurately tracks hanger angles under all conditions.



Aerospace
Division

An IC Industries Company

A P P E N D I X

| | | | |
|------------------------------|---|---------------------------------------|------------------------------|
| DATE 5.9.83 | CONDUCTED BY CS | PURPOSE OF TEST CALIBRATION | PAGE 1 OF |
| TEST STAND NO. ±18 | TEST CONDITIONS 150°F ↔ STAT.C HGR VOLT +3.69 | | UNIT TYPE AP27VP-2 |
| | | SERIAL NO. 152294 | LAB. NO. 5177 |

| SPEED | | INLET | | | OUTLET | | | | DRAIN | | | | TORQUE IN-LB | | MA. | O.EFF. | K/T. | Hgr | Btu | LWS |
|-------|------|-------|-----|-------|--------|------|------------|-------|-------|------|------|-------|-----------------|------|------|--------|-------|-------|-----|-----|
| | | FLOW | | PRESS | TEMP | FLOW | | PRESS | TEMP | FLOW | | PRESS | | | | | | | | |
| RPM | | CPS | GPM | | °F | CPS | GPM | PSIG | °F | CPS | GPM | | °F | | | | | | | |
| 1 | 3917 | | | 60 | 155 | 120 | 69.1 | 2850 | | 94 | .49 | 105 | | 264 | 0 | 87.7 | +3.76 | 19.5° | 670 | 1 |
| 2 | 3918 | | | 60 | 150 | 900 | 51.5 | 3020 | | 21 | .11 | 90 | | 165 | 0 | 86.7 | +1.97 | 15.0 | 577 | 2 |
| 3 | 3917 | | | 60 | 150 | 600 | 34.2 | 3030 | | 118 | .62 | 75 | | 1134 | 0 | 84.1 | +0.15 | 10.2° | 475 | 3 |
| 4 | 3915 | | | 60 | 155 | 300 | 17.0 | 3040 | | 205 | 1.07 | 70 | | 634 | 0 | 75.1 | +1.70 | 5.5° | 417 | 4 |
| 5 | 3916 | | | 60 | 149 | | 0 | 3050 | | 282 | 1.45 | 66 | | 138 | 0 | 0 | -3.53 | 0.7° | 363 | 5 |
| 6 | | | | | | | | | | | | | | | | | | | | 6 |
| 7 | | | | | | | | | | | | | | | | | | | | 7 |
| 8 | 3920 | | | 60 | 156 | 1223 | 70.1 19 | 1900 | | 133 | .70 | 96 | | 1460 | 3.05 | 82.9 | +3.75 | 19.5° | 656 | 8 |
| 9 | 3919 | | | 60 | 152 | 900 | 51.9 | 2060 | | 29 | .15 | 86 | | 1176 | 3.05 | 82.9 | +1.85 | 14.4 | 531 | 9 |
| 10 | 3919 | | | 60 | 149 | 600 | 34.2 | 2050 | | 51 | .27 | 76 | | 798 | 3.05 | 80.1 | +0.07 | 10.1 | 420 | 10 |
| 11 | 3917 | | | 60 | 149 | 300 | 17.0 | 2040 | | 127 | .66 | 67 | | 446 | 3.05 | 70.8 | +1.79 | 5.3 | 343 | 11 |
| 12 | 3917 | | | 60 | 155 | | 0 | 2060 | | 210 | 1.10 | 65 | | 118 | 3.05 | 0 | -3.62 | 0.5 | 311 | 12 |
| 13 | | | | | | | | | | | | | | | | | | | | 13 |
| 14 | | | | | | | | | | | | | | | | | | | | 14 |
| 15 | | | | | | | | | | | | | | | | | | | | 15 |

ORIGINAL
OF POOR

ORIGINAL PAGE 19
OF POOR QUALITY

| | | | |
|-----------------------------|--|---------------------------------------|---|
| DATE 5-10-83 | CONDUCTED BY CS | PURPOSE OF TEST CALIBRATION | PAGE 2 OF UNIT TYPE |
| TEST STAND NO. #8 | TEST CONDITIONS 150°F ↔ STATIC ±192 VOLT +3.70 | | SERIAL NO. 152294 LAB. NO. 5177 |

| SPEED | INLET | | | OUTLET | | | | DRAIN | | | | TORQUE IN-LB | Hgr | MA | VOLT | O.EFF | LOSS BTU | |
|---------|-------|-----|-------|--------|------|------|--------|-------|------|------|-------|-----------------|------|------|------|-------|-------------|------|
| | FLOW | | PRESS | TEMP | FLOW | | PRESS | TEMP | FLOW | | PRESS | | | | | | | TEMP |
| RPM | CPS | GPM | | °F | CPS | GPM | PSIG | °F | CPS | GPM | | °F | | | | | | |
| 1 3919 | | | 60 | 157 | 850 | 70.6 | 970 | | 118 | .62 | 106 | | 792 | 195 | 5.50 | +3.75 | 76.1 | 497 |
| 2 3918 | | | 60 | 157 | 622 | 52.9 | 1020 | | 23 | .12 | 90 | | 626 | 15.0 | 5.50 | +1.97 | 76.1 | 393 |
| 3 3918 | | | 60 | 158 | 415 | 35.3 | 1000 | | 32 | .17 | 75 | | 448 | 10.2 | 5.50 | +0.09 | 69.5 | 360 |
| 4 3918 | | | 60 | 149 | 207 | 17.6 | 1050 | | 85 | .44 | 70 | | 262 | 5.2 | 5.50 | -1.86 | 62.4 | 359 |
| 5 3916 | | | 60 | 149 | | 0 | 1050 | | 166 | .87 | 66 | | 86 | 0.3 | 5.50 | -3.69 | 0 | 227 |
| 6 | | | | | | | | | | | | | | | | | | |
| 7 | | | | 225°F | | | STATIC | | | | | | | | | +3.75 | | |
| 8 3920 | | | 60 | 224 | 803 | 68.3 | 2850 | | 14 | .07 | 95 | | 204 | 19.7 | 0 | +3.80 | 87.5 | 672 |
| 9 3920 | | | 60 | 230 | 600 | 51.0 | 2990 | | 95 | .50 | 85 | | 1574 | 15.4 | 0 | +2.08 | 88.0 | 504 |
| 10 3916 | | | 60 | 220 | 400 | 34.0 | 3010 | | 221 | 1.15 | 81 | | 1020 | 10.7 | 0 | +6.29 | 86.4 | 391 |
| 11 3917 | | | 460 | 221 | 200 | 17.0 | 3020 | | 326 | 1.67 | 70 | | 596 | 6.0 | 0 | -1.55 | 79.3 | 325 |
| 12 3917 | | | 60 | 225 | | 0 | 3030 | | 417 | 2.11 | 70 | | 134 | 1.3 | 0 | -3.27 | 0 | 353 |
| 13 | | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | | | |
| 15 | | | | | | | | | | | | | | | | | | |

ORIGINAL PAGE IS
OF POOR QUALITY

| | | | |
|------------------------------|-----------------------------------|---------------------------------------|--|
| DATE 5-10-83 | CONDUCTED BY GS | PURPOSE OF TEST CALIBRATION | PAGE 3 OF UNIT TYPE |
| TEST STAND NO. ± 8 | TEST CONDITIONS 225°F ← | | SERIAL NO. AP27VP-2 152294 LAB. NO. 5177 |

| SPEED | | INLET | | | OUTLET | | | | DRAIN | | | | TORQUE IN-LB | O. EFF | MA | Hgr | VOLT | Loss Btu | | |
|-------|------|-------|-----|-------|--------|------|------|-------|-------|------|------|-------|-----------------|--------|------|------|------|-------------|-----|------|
| | | FLOW | | PRESS | TEMP | FLOW | | PRESS | TEMP | FLOW | | PRESS | | | | | | | | TEMP |
| RPM | | CPS | GPM | | °F | CPS | GPM | PSIG | °F | CPS | GPM | | °F | | | | | | | |
| 1 | 3919 | | | 60 | 220 | 817 | 69.5 | 1900 | | 61 | .32 | 90 | | 1386 | 86.6 | 3.48 | 19.7 | 3.79 | 489 | 1 |
| 2 | 3919 | | | 60 | 219 | 600 | 51.0 | 2040 | | 30 | .16 | 86 | | 1096 | 86.5 | 3.48 | 15.0 | 1.93 | 390 | 2 |
| 3 | 3916 | | | 60 | 230 | 400 | 34.0 | 2060 | | 133 | .70 | 75 | | 764 | 83.6 | 3.48 | 10.2 | 0.17 | 331 | 3 |
| 4 | 3920 | | | 60 | 222 | 200 | 17.0 | 2040 | | 224 | 1.16 | 70 | | 402 | 78.6 | 3.48 | 5.5 | 1.70 | 227 | 4 |
| 5 | 3920 | | | 60 | 224 | | 0 | 2060 | | 296 | 1.52 | 69 | | 128 | 0 | 3.48 | 1.4 | 3.23 | 337 | 5 |
| 6 | | | | | | | | | | | | | | | | | | | | 6 |
| 7 | | | | | | | | | | | | | | | | | | | | 7 |
| 8 | 3920 | | | 70 | 221 | 829 | 70.5 | 970 | | 17 | .09 | 95 | | 762 | 78.2 | 5.78 | 19.4 | 3.71 | 438 | 8 |
| 9 | 3922 | | | 70 | 218 | 600 | 51.0 | 970 | | 33 | .17 | 90 | | 582 | 74.0 | 5.78 | 14.8 | 1.89 | 398 | 9 |
| 10 | 3922 | | | 70 | 222 | 400 | 34.0 | 1070 | | 82 | .43 | 85 | | 441 | 71.9 | 5.78 | 10.2 | 0.12 | 329 | 10 |
| 11 | 3923 | | | 70 | 218 | 200 | 17.0 | 1050 | | 137 | .72 | 78 | | 241 | 63.6 | 5.78 | 5.3 | 1.83 | 236 | 11 |
| 12 | 3920 | | | 70 | 220 | | 0 | 1060 | | 220 | 1.15 | 75 | | 78 | 0 | 5.78 | 0.5 | 3.61 | 205 | 12 |
| 13 | | | | | | | | | | | | | | | | | | | | 13 |
| 14 | | | | | | | | | | | | | | | | | | | | 14 |
| 15 | | | | | | | | | | | | | | | | | | | | 15 |

ORIGINAL PAGE IS
OF POOR QUALITY

| | | | |
|-----------------------|----------------------------|--------------------------------|-------------------|
| DATE 5-12-83 | CONDUCTED BY GS | PURPOSE OF TEST CALIBRATION | PAGE 7 OF |
| TEST STAND NO. 118 | TEST CONDITIONS 225°F → | | UNIT TYPE |
| | | | AP-21VP-2 |
| | | | SERIAL NO. 152294 |
| | | | LAB. NO. 5177 |

| SPEED | INLET | | | | OUTLET | | | | DRAIN | | | | TORQUE | | | MA | VOLT | | |
|---------|-------|-----|-------|------|--------|------|-------|------|-------|------|-------|------|--------|-----|--|------|------|------|------|
| | FLOW | | PRESS | TEMP | FLOW | | PRESS | TEMP | FLOW | | PRESS | TEMP | | | | | | | |
| RPM | CPS | GPM | | °F | CPS | GPM | PSIG | °F | CPS | GPM | | °F | IN-LB | | | ↓ | ↑ | ↓ | ↑ |
| 1 1805 | | | 60 | 220 | 59 | 5.0 | 3010 | | 299 | 1.53 | 69 | | 418 | 415 | | 0 | 1.68 | 2.09 | 2.08 |
| 2 1804 | | | 60 | 220 | 59 | 5.0 | 3000 | | 297 | 1.52 | 69 | | 418 | 420 | | 1.83 | 1.78 | 2.08 | 2.07 |
| 3 1804 | | | 60 | 219 | 59 | 5.0 | 2500 | | 252 | 1.30 | 67 | | 334 | 340 | | 2.64 | 2.56 | 2.16 | 2.16 |
| 4 1804 | | | 60 | 218 | 59 | 5.0 | 2000 | | 217 | 1.13 | 65 | | 260 | 264 | | 3.44 | 3.32 | 2.25 | 2.29 |
| 5 1804 | | | 60 | 216 | 59 | 5.0 | 1500 | | 175 | .92 | 65 | | 190 | 194 | | 4.27 | 4.15 | 2.34 | 2.34 |
| 6 1804 | | | 60 | 215 | 59 | 5.0 | 1000 | | 134 | .70 | 62 | | 128 | 130 | | 5.02 | 4.98 | 2.41 | 2.42 |
| 7 | | | | | | | | | | | | | | | | | | | |
| 8 1802 | | | 60 | 223 | 177 | 15.0 | 2990 | | 208 | 1.09 | 68 | | 428 | 424 | | 0 | 2.06 | 0.26 | 0.21 |
| 9 1801 | | | 60 | 221 | 177 | 15.0 | 2500 | | 181 | .95 | 67 | | 850 | 858 | | 2.71 | 2.68 | 0.17 | 0.18 |
| 10 1804 | | | 60 | 218 | 177 | 15.0 | 2000 | | 147 | .77 | 66 | | 462 | 468 | | 3.56 | 3.48 | 0.06 | 0.07 |
| 11 1804 | | | 60 | 223 | 177 | 15.0 | 1500 | | 129 | .67 | 66 | | 442 | 446 | | 4.27 | 4.20 | 0.02 | 0.01 |
| 12 1803 | | | 60 | 226 | 177 | 15.0 | 1000 | | 98 | .51 | 65 | | 322 | 326 | | 5.09 | 5.07 | 0.07 | 0.05 |
| 13 | | | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | | | | |
| 15 | | | | | | | | | | | | | | | | | | | |

ORIGINAL PAGE 18
OF POOR QUALITY

| | | | |
|----------------------|---|--------------------------------|------------------------|
| DATE 5-12-83 | CONDUCTED BY GS | PURPOSE OF TEST CALIBRATION | PAGE 9 OF UNIT TYPE |
| TEST STAND NO. #8 | TEST CONDITIONS 225°F ← → HYSTERESIS | | AP27VP.2 |
| | | SERIAL NO. 152294 | LAB. NO. 5177 |

| SPEED | INLET | | | | OUTLET | | | | DRAIN | | | | TORQUE | | | MA | | VOLT | | |
|----------|-------|-----|-------|------|--------|-----|-------|------|-------|------|-------|------|---------|--|--|------|------|------|------|----|
| | FLOW | | PRESS | TEMP | FLOW | | PRESS | TEMP | FLOW | | PRESS | TEMP | | | | | | | | |
| RPM | CPS | GPM | | °F | CPS | GPM | PSIG | °F | CPS | GPM | | °F | IN-LB | | | ↓ | ↑ | ↓ | ↑ | |
| 1 4008 | | | 60 | 224 | 59 | 5 | 3020 | | 373 | 2.00 | 69 | | 250 256 | | | 1.58 | 2.92 | 2.92 | | 1 |
| 2 4007 | | | 60 | 215 | 59 | 5 | 3000 | | 368 | 1.87 | 68 | | 252 254 | | | 1.70 | 1.68 | 2.94 | 2.92 | 2 |
| 3 4004 | | | 60 | 219 | 59 | 5 | 2500 | | 333 | 1.70 | 65 | | 212 214 | | | 2.64 | 2.64 | 2.97 | 2.97 | 3 |
| 4 4004 | | | 60 | 226 | 59 | 5 | 2000 | | 284 | 1.46 | 65 | | 172 174 | | | 3.43 | 3.39 | 3.04 | 3.04 | 4 |
| 5 4002 | | | 60 | 215 | 59 | 5 | 1500 | | 214 | 1.12 | 65 | | 144 146 | | | 4.40 | 4.31 | 3.12 | 3.13 | 5 |
| 6 4002 | | | 60 | 215 | 59 | 5 | 1000 | | 200 | 1.05 | 63 | | 122 122 | | | 5.92 | 5.80 | 3.17 | 3.17 | 6 |
| 7 | | | | | | | | | | | | | | | | | | | | 7 |
| 8 4001 | | | 60 | 216 | 177 | 15 | 3030 | | 323 | 1.65 | 67 | | 542 544 | | | 1.63 | 1.86 | 1.85 | | 8 |
| 9 4001 | | | 60 | 229 | 177 | 15 | 3000 | | 351 | 1.79 | 66 | | 532 538 | | | 1.82 | 1.72 | 1.87 | 1.86 | 9 |
| 10 4000 | | | 60 | 224 | 177 | 15 | 2500 | | 293 | 1.50 | 66 | | 456 454 | | | 2.63 | 2.65 | 1.90 | 1.91 | 10 |
| 11 4004 | | | 60 | 216 | 177 | 15 | 2000 | | 225 | 1.17 | 66 | | 366 366 | | | 3.39 | 3.40 | 2.00 | 1.99 | 11 |
| 12 4008 | | | 60 | 225 | 177 | 15 | 1500 | | 188 | .98 | 65 | | 290 288 | | | 4.47 | 4.46 | 2.05 | 2.06 | 12 |
| 13 11008 | | | 60 | 215 | 177 | 15 | 1000 | | 156 | .82 | 65 | | 220 220 | | | 5.92 | 5.85 | 2.11 | 2.11 | 13 |
| 14 | | | | | | | | | | | | | | | | | | | | 14 |
| 15 | | | | | | | | | | | | | | | | | | | | 15 |

ORIGINAL PAGE 13
OF POOR QUALITY